



UTD-250

LED Ultra-Thin Power Supply(C&V)

- Universal AC input(Voltage range)100-277VAC
- Built in active PFC function
- Efficiency up to 93%, super thin and small size.
- Protection:short circuit/over load/over voltage/over temperature
- IP67 design for indoor or outdoor installation
- It can be used in dry, wet and rainy environment
- Cooling by free air, high reliability
- Up to 50000-hour life time
- Suitable for internal lights application for 1/1/1/1.
- Widely used in LED lighting and IT equipment.
- Compliance to worldwide safety regulation for led lightings.



100-277VAC

PF>0.96

THD<5%



CE CB SELV IP67




Specification


Model	UTD-12-250	UTD-24-250	UTD-36-250	UTD-48-250	
OUTPUT	Output voltage	12VDC	24VDC	36VDC	48VDC
	Output voltage range	12VDC±0.3VDC	24VDC±0.4VDC	36VDC±0.5VDC	48VDC±1.2VDC
	Output current	Max 21A	Max 10.5A	Max 7A	Max 5.2A
	Output power	Max 250W			
	Output power range	0-250W			
	Ripple & Noise	<±50mV	<±50mV	<±50mV	<±50mV
	Linear Regulation	±1%			
	Load Regulation	±1%			
	Start-up Time [Typ]	600ms/230VAC 800ms/115VAC			
	Rise Time [Typ]	50ms/230VAC 50ms/115VAC			
INPUT	Input voltage	100-277VAC			
	Frequency	50/60Hz			
	Input current	2.81-1.08A			
	Power factor	PF>0.96/230VAC, at full load;	PF>0.96/115VAC, at full load;		
	No-load power consumption	<0.5W			
	THD	<5% at 230VAC, at full load;	<5% at 115VAC, at full load;		
	Efficiency [Typ.]	93%	93.5%	94%	94%
	Inrush current [Typ.]	55A/230VAC			
	Control surge capability	L-N:20V L-N-PE:4kV			
	Leakage current	Max. 0.5mA			
ENVIRONMENT	Working temperature	ta: -30°C -58°C tc: 80°C			
	Working humidity	20 - 95%RH, condensing (Waterproof)			
	Storage temp., humidity	-40°C - 80°C, 10-95%RH			
	Vibration	10-500Hz, 2G 12min./1cycle, period for 72min., each along X, Y, Z axes.			
PROTECTION	Over temperature	Protection type: Turn off the output voltage, after the temperature drops, re-energize to restore.			
	Over voltage protection	Output voltage a 15-18V, turn off the output, after the abnormality is eliminated, re-energize to recover.	Output voltage <29-35V, turn off the output, after the abnormality is eliminated, re-energize to recover		
	Over load protection	Shut down the output when current load a 110%-150%, auto recovers.			
	Short circuit protection	Protection type: It can be automatically restored after the fault is eliminated.			
SAFETY & EMC	Withstand voltage	IP-GIP, 2050VAC			
	Isolation resistance	IP-GIP: 180MΩ/500VDC/25°C/70%RH			
	Safety standards	IEC/EN61347; IEC/EN60950; IP67			
	EMC emission	EN55015:2013; FCC Part 15B; EN61547:2009; EN61000-3-2:2014; EN61000-3-3:2013			
EMC immunity	EN61000-4-2, 3, 4, 5, 6, 8, 11 EN61547				
Reliability and Quality Control	Impact aging	100% of the product is fully loaded and impacted for 4 hours under an environment of at least 0°C ±5°C			
	Component derating	Under the steady-state conditions of rated input and output, the stress of components will not exceed its maximum nominal value			
NOTE	1. All parameters not specifically mentioned are measured at 230VAC input, rated load and 25°C ambient temperatures.				
	2. Ripple and noise test method: connect 0.1µF and 47µF capacitors in parallel at the terminal, and measure under 20MHz bandwidth.				
	3. Ensure that the power supply is used under the rated parameters and environment.				

Dimensions

Unit:mm



Relationship diagrams



Packaging Information

DIMENSION	242x67x22.8mm(LxWxH)
PACKING	275x80x27mm(LxWxH)
CARTON QUANTITY	30PCS
CARTON SIZE	435x290x180mm(LxWxH)
WEIGHT	780g±10g/PCS

